

PEF Rod

P.E.F. Foam Backer

Masons™ PEF Rod is a cylindrical flexible closed cell polyethylene material, available in various diameters from 6mm to 50mm.

Masons PEF Rod is used around windows, doors or other penetration openings. It ensures the sealant does not completely fill the cavity.

Masons™ PEF Rod provides the following functions:

- Limits the amount and depth of the sealant applied into the joint.
- Acts as a bond break to allow joint movement without undue stress to sealant.
- Acts as a barrier to the flow of sealant through a joint.
- Will assist in providing an around the window frame and penetrations through walls.
- For use with pre-cast concrete slabs and joints between brick and masonry.

PEF Rod - Advantages

- Weather resistant
- No water absorption, closed cell
- Easy to install
- Wide range of sizes available
- Non toxic, odourless
- Resistant to most chemicals
- Easily compressible, good expansion
- Very light weight

Diameter	Roll Length	Bunnings Code
6mm	20m	00306837
6mm	50m	00306893
8mm	20m	00306845
8mm	50m	00306840
10mm	20m	00306857
10mm	50m	00306854
13mm	20m	00306865
13mm	50m	00306860
15mm	20m	00306871
15mm	50m	00306868
20mm	20m	00306874
25mm	10m	00306877
30mm	10m	00306882
40mm	10m	00306887
50mm	5m	00306890

