

## ***Paslode® FrameMaster-Li™ PowerVent Framing Nailer***

### **Paslode Impulse Gas Technology**

Portable, no need for heavy compressors or awkward air lines

### **Lithium-Ion Battery Technology**

Up to 9,000 nails per charge  
Charge in 1 hour

### **Low Tool Actuation Pressure**

Reduces operator fatigue

### **Tool-Free Depth of Drive Adjustment**

Five depth of drive settings  
Greater flexibility for nail placement and a superior finish

### **Suitable for 44 to 90mm Length Nails**

Full range of 50 to 90mm nails in bright, galvanised, and stainless steel  
Product Nail Guide attachment (B20540P) required to drive 44mm product nails

### **Suitable for 2.8 to 3.15mm Diameter Nails**

### **Nail Lock Out Bar**

Eliminates blank tool firing  
Protects timber and tool

### **Optimum Skew Nailing Teeth Placement**

Helps grip timber to ensure positive placement of the fastener

### **Ergonomic Design**

Operator friendly  
Non-slip handgrip and trigger improves comfort and safety

### **On / Off Battery Positions**

Improved safety and battery conservation

### **Reversible Belt and Rafter Hook**

Safely secures tool on timber framing  
Secures tool on tool belt for convenience



Two Lithium-Ion batteries included with tool



***Product Code***

***Model Description***

***Barcode***

B20543P

Paslode Impulse FrameMaster-Li PowerVent Framing Nailer

9315104016934

The information presented in this product information sheet is correct as at the date of publication. Paslode reserves the right to change performance, product or content information without notice. **Read all safety instructions.**



## ***Impulse® FrameMaster-Li™ PowerVent Framing Nailer***

### ***Specifications***

Product Size (WxHxD)	310 x 386 x 105mm
Packaged Size (WxHxD)	468 x 458 x 149mm
Tool Weight (with battery)	3.3kg
Packaged Weight	6.48kg
Quantity Per Pack	1
Cycle Rate	2-3 nails per second
Tool Duty Cycle Rate	1000 shots per hour
Magazine Capacity	40 nails (1 strip)
Nail Range Length	44 – 90mm
Nail Range Diameter	2.87 – 3.15mm
Battery	7.4 Volt DC 2150mAh Lithium-Ion (B20543A)
Battery Recharge Time	1 hour
Fuel Cell	Paslode Impulse Power+ Fuel Cell (B20543F)
Propellant	Liquid Hydrocarbon
Fuel Cell & Battery Storage Temperature	Below 49°C
Rated Input Voltage Battery Charger Base	12 Volt DC @ 1.8A
Rated Output Voltage Battery Charger Base	8.5 Volt DC @ 2.0A
Rated Input Voltage Power Adaptor	240 Volt AC 50 to 60Hz 30W
Rated Output Voltage Power Adaptor	12 Volt DC 1.8A

### ***Capacity***

Battery Capacity	Up to 9,000 nails per charge
Fuel Cell Capacity	Up to 1,200 nails per cell

### ***Applications***

Framing (incl. Hardwood and LVL)
Flooring, Roofing, Decking, Cladding

The information presented in this product information sheet is correct as at the date of publication. Paslode reserves the right to change performance, product or content information without notice. **Read all safety instructions.**