



Hydro™

Bituminous Flashing Tape



Hydro Flashing Tape is a 1mm thick self adhesive bituminous flashing tape to seal around windows, doors, and other joinery openings as a secondary defence against water penetration. Adhesion from 5°C.

- It's suitable for timber and steel framed buildings
- Has been tested and passed by **CodeMark**
- For a risk score between 0-20 in accordance with NZBC Acceptable Solution E2/AS1
- Passed NZS3604 Building Wind Zones up to and including 'Very High'

Hydro™ Flashing Tape- Advantages

- **Compatible** with all building wraps
- Simple 4 step installation, save time reducing costs
- 1mm thick adhesive layer
- Reliable and dependable weather tightness
- Works in temperatures from **5°C**
- An *Optional* **Corner Guard** is easy to install and increases protection to framing



Corner Guard



Scope of Use / Applications

Windows/Door/Timber & Steel Frame Flashings

Masons Hydro Flashing Tape and Masons Corner Guard must be installed in accordance with the instructions outlined on page 16 of this catalogue.

WARNING: Don't apply any solvent based glues or adhesives/sealants to the tape as it will react with the bitumen.

**Note: 150mm Wide tape is used for 100mm wide window or door framing.
200mm wide tape is used for 140mm-150mm wide levels.**

Hydro flashing tape	Roll Sizes	Bunnings Code
Hydro flashing tape 75mm	H 75mm x L 25m	00281799
Hydro flashing tape 100mm	H 100mm x L 25m	00281802
Hydro flashing tape 150mm	H 150mm x L 25m	00281811
Hydro flashing tape 150mm	H 150mm x L 10m	00290611
Hydro flashing tape 200mm	H 200mm x L 25m	00281818
Hydro corner guards	50	00290608