



SAFETY DATA SHEET

SECTION 1 IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product Identifier ACETONE

Other Names 2-Propanone, Dimethyl Ketone

Manufacturer's Product Code 16255

Recommended Use Solvent

Details of Supplier/Manufacturer

appnon/manaractaron	
Company:	Recochem Inc. ABN: 69 010 485 999
Address:	1809 Lytton Road, Lytton, Queensland 4178, Australia
Phone:	+617 3308 5200 Fax: +617 3308 5201
Website:	www.recochem.com.au

Details of Distributor

Company:	Owens Logistics
Address:	3-5 Kahu Street, Otahuhu, Auckland
Phone:	(09) 270 1310 Fax: (09) 270 1311

Emergency Telephone Numbers

Poisons	0800 764 766	
Information:	0800 704 700	

SECTION 2 HAZARDS IDENTIFICATION

Hazardous chemical	according to classification by Safe Work Australia
Dangerous goods	according to the Australian Code for the Transport of Dangerous Goods by Road and Rail

Signal Word

GHS Classification	Pictogram	Hazard statement
Flammable Liquids, Category 2	FLAME	H225 Highly flammable liquid and vapour
Serious Eye Damage/Irritation, Category 2A		H319 Causes serious eye irritation
Specific Target Organ Toxicity (Single exposure), Category 3	EXCLAMATION MARK	H336 May cause drowsiness or dizziness

Page 1 of 7 ISSUE: 2 ISSUE DATE: 10/12/2014

Non-GHS (Safe Work Australia)	N/A	AUH066 Repeated exposure may cause skin dryness or cracking
-------------------------------	-----	---

Precautionary statements:

GENERAL	
P101	If medical advice is needed, have product container or label at hand
P102	Keep out of reach of children
P103	Read label before use
PREVENTATIVE	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilation/lighting equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P261	Avoid breathing mist/vapours/spray
P264	Wash thoroughly after handling
P271	Use only outdoors or in a well-ventilated area
P280	Wear protective gloves/eye protection/face protection
RESPONSE	
P303 + P361 + P353	IF ON SKIN (or hair): Take off contaminated clothing and wash before reuse. Rinse skin with water/shower
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P337 + P313	If eye irritation persists: Get medical advice/attention
P370 + P378	In case of fire: Use foam/water spray/fog for extinction
STORAGE	
P403 + P233	Store in a well-ventilated place. Keep container tightly closed
P403 + P235	Store in a well-ventilated place. Keep cool
P405	Store locked up
DISPOSAL	
P501	Dispose of contents/container in accordance with local regulations

SECTION 3 COMPOSITION AND INFORMATION ON INGREDIENTS

Ingredients Names and Proportions

Chemical Entity	CAS Number	Proportion (%)
Acetone	67-64-1	> 99

SECTION 4 FIRST AID MEASURES

Description of necessary first aid measures

Inhalation:	Keep victim calm and remove to fresh air if safe to do so. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
Skin Contact:	If skin contact occurs, remove contaminated clothing and wash skin thoroughly with water and follow by washing with soap if available. Transport to nearest medical facility for additional treatment if necessary.
Eye Contact:	If in eyes, hold eyes open, flood with water for at least 15 minutes. Seek immediate medical assistance.

Page 2 of 7 ISSUE: 2 ISSUE DATE: 10/12/2014

Ingestion:	If swallowed, do NOT induce vomiting. Transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below
	hips to prevent aspiration.

Symptoms caused by exposure

Inhalation:	Breathing of high vapour concentrations may cause central nervous system depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continuous inhalation may result in unconsciousness and death.
Skin:	May include burning sensation and/or a dried/cracked appearance.
Eye:	May include burning sensation, redness, swelling and/or blurred vision.
Ingestion:	May include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath and/or fever

Medical attention and special treatment

Treat symptomatically.

SECTION 5 FIRE FIGHTING MEASURES

Suitable extinguishing equipment

Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Specific hazards arising from the chemical

A highly flammable liquid. Carbon monoxide and/or carbon dioxide may be evolved. May form flammable vapour mixture with air. Avoid all ignition sources. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Heating can cause expansion or decomposition leading to violent rupture of containers. Containers exposed to intense heat from fires should be cooled with large quantities of water.

Special protective equipment and precautions for fire fighters

Wear full protective clothing and self-contained breathing apparatus. Hazchem code •2YE.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Avoid contact with spilled or released material. Shut off leaks, if possible without personal risks. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Remove all sources of ignition in the surrounding area. Take precautionary measure against static discharge. Ensure electrical continuity by bonding and earthing all equipment.

Environmental precautions

Use appropriate containment to avoid environmental contamination. Prevent from spreading and entering waterway using sand, earth or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Ventilate contaminated area thoroughly.

Methods and materials for containment and cleaning up

For small spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

For larger spills (> 1 drum), transfer by means such as a vacuum truck to a salvage tank for recovery or disposal. Do not flush residues with water. Retain as contaminated waste. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

Page 3 of 7 ISSUE: 2 ISSUE DATE: 10/12/2014

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Highly flammable product. Avoid breathing vapours. Handle and open containers with care in a well-ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Do not eat, drink or smoke in contaminated areas. Electrostatic charges may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by earthing all equipment. Flameproof equipment necessary in area where chemical is being used. Vapours may accumulate in low or confined areas.

Conditions for safe storage, including any incompatibilities

Bulk storage tanks should be bunded. Store in a well-ventilated area, away from sunlight, ignition sources and other sources of heat. Do not store near strong oxidants.

SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure control measures

From National Occupational Health & Safety Commission (NOHSC) Worksafe Australia - Acetone: 1185mg/m³ (500ppm) TWA (8hr), STEL 2375mg/m³ (1000ppm)

Biological monitoring

No biological limit allocated.

Engineering controls

Ensure that adequate ventilation is provided. Avoid generating and inhaling mists and vapours. Keep containers closed when not in use.

Individual protection measures

Eye and face protection:	Wear safety goggles.
Skin protection:	Use solvent resistant gloves, nitrile for longer term protection or PVC and neoprene for incidental splashes.
Respiratory protection:	If work practices do not maintain airborne level below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point > 65°C). Respirators should comply with AS1716 or an equivalent approved by a state/territory authority.
Thermal hazards:	Not applicable.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear colourless liquid
Odour:	Characteristic
Odour threshold (ppm):	Data not available
pH:	Not applicable
Melting point/freezing point (°C):	-95
Initial boiling point and boiling range (°C):	56
Flash point (°C):	-18 (closed cup)
Evaporation rate (Butyl acetate = 1):	5.6
Flammability:	Highly flammable
Upper/lower flammability or explosive limits (%):	2.15 - 13.0

Page **4** of **7** ISSUE: 2 ISSUE DATE: 10/12/2014

Vapour pressure (mbar @ 20°C):	186
Vapour density (air = 1):	2
Density (g/ml @ 20°C):	0.79
Solubility:	Miscible with water
Partition coefficient: n-octanol/water:	0.2
Auto-ignition temperature (°C):	465
Decomposition temperature (°C):	Data not available
Kinematic viscosity (mm²/s @ 20°C):	Data not available

SECTION 10 STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions of use.

Chemical stability

Stable under normal conditions of use.

Possibility of hazardous reactions

Stable under normal conditions of use.

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

Incompatible materials

Strong oxidising agents, reducing agents, acids, alkalis.

Hazardous decomposition products

Burning can produce carbon monoxide and/or carbon dioxide.

SECTION 11 TOXICOLOGICAL INFORMATION

	Low toxicity -
Acute toxicity:	LD50 Oral (rat) > 2000 mg/kg
Acute toxicity.	LC50 Inhalation (rat, 4h) > 20 mg/l
	Skin - rabbit, Result – Irritating to skin (48h).
Skin corrosion/irritation:	May cause skin irritation. Will have a degreasing effect on the skin.
Skiii corrosion/iintation.	Repeated or prolonged skin contact may lead to irritant contact dermatitis
Corious ava	, , ,
Serious eye	Moderate to severe eye irritant. High concentrations of 500-1000ppm are
damage/irritation:	irritating to eyes
Respiratory or skin	Not expected to be a sensitiser
sensitisation:	The expected to be a continued.
Germ cell mutagenicity:	Not mutagenic
Carcinogenicity:	Not expected to be carcinogenic
Reproductive toxicity:	Not expected to impair fertility
<u> </u>	
Specific Target Organ	
Toxicity (STOT) -	Data not available
single exposure:	
Specific Target Organ	Central nervous system: repeated exposure affects the nervous system.
Toxicity (STOT) –	Effects seen at high doses only
repeated exposure:	Lifeoto seen at high doses only
Aspiration bazard:	Aspiration into the lungs when swallowed or vomited may cause chemical
Aspiration hazard:	pneumonitis which can be fatal

Page 5 of 7 ISSUE: 2 ISSUE DATE: 10/12/2014

SECTION 12 ECOLOGICAL INFORMATION

Ecotoxicity

Acute toxicity:

Fish –	Low toxicity: LC/EC/IC50 > 1000mg/l
Aquatic invertebrate –	Low toxicity: LC/EC/IC50 > 1000mg/l
Algae –	Low toxicity: LC/EC/IC50 > 1000mg/l
Microorganisms –	Low toxicity: LC/EC/IC50 > 1000mg/l

Chronic toxicity:

Fish –	Data not available
Aquatic invertebrate –	Data not available
Algae –	Data not available
Microorganisms –	Data not available

Persistence and degradability

Readily biodegradable.

Bioaccumulative potential

Not expected to bioaccumulate significantly.

Mobility in soil

Miscible with water. If product enters soil, it will be mobile and may contaminate groundwater.

Other adverse effects

Data not available.

SECTION 13 DISPOSAL CONSIDERATIONS

Ensure waste disposal conforms to local waste disposal regulations.

SECTION 14 TRANSPORT INFORMATION

UN number:	1090
Proper shipping name:	Acetone
Australian Dangerous Goods class:	3
Australian Dangerous Goods packing group:	II
Hazchem code:	•2YE

SECTION 15 REGULATORY INFORMATION

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP), Poisons Schedule:	5
Australian Inventory of Chemical Substances (AICS):	Listed
Dangerous Goods Initial Emergency Response Guide (SAA/SNZ HB76):	14
New Zealand HSNO, Classification:	3.1B, 6.1E (oral), 6.3B, 6.4A

Page 6 of 7 ISSUE: 2 ISSUE DATE: 10/12/2014

SECTION 16 OTHER INFORMATION

Date of preparation:	10/12/2014
Revision number:	2
Changes in this revision:	Update to GHS SDS standard

This MSDS summarises product safety information at the date of issue, to the best of our knowledge, as a general guide. Recochem cannot anticipate or control the conditions under which the product is used, so prior to usage each user must assess and control the risks associated with their use of the product. Users should also consult the relevant legislation governing the use and storage of this product. We make no warranties, express or implied, and assume no liability in connection with any use of information contained within this document. If clarification or further information is needed, the user should contact Recochem on +617 3308 5200.

Page **7** of **7** ISSUE: 2 ISSUE DATE: 10/12/2014