



Fernco®

The Fernco PlumbQwik Range



- Quick and easy to install for a leakproof seal
- Ideal for emergency repairs
- Series 316 Stainless Steel
- AS/NZ 4327:1995
- Metal banded flexible couplings for low pressure applications
- Corrosion resistant and rust proof
- No special tools are needed, can be installed easily with a screw driver or 5/16" (7.93mm) nut driver or socket (to 50inch/lbs torque.)

PRODUCT	CODE	DESCRIPTION & NOMINAL SIZE	ACTUAL SIZE	MIN	MAX	MIN	MAX
GREY PLUMBQWIK COUPLINGS							
FOR JOINING PVC TO PVC OR COMBINATIONS OF PVC, CAST IRON, COPPER AND GAL - 50 TO 225mm DIAMETER							
	F1056-32M	32mm PVC-PVC	38 x 38mm	34mm	43mm		
	F1056-40M	40mm PVC-PVC	45 x 45mm	37mm	45mm		
	F1056-50M	50mm PVC-PVC	55 x 55mm	55mm	58mm		
	F1056-65M	65mm PVC-PVC	70 x 70mm	62mm	70mm		
	F1056-80M	80mm PVC-PVC	85 x 85mm	76mm	84mm		
	F1056-90M	90mm PVC-PVC	91 x 91mm	81mm	91mm		
	F1056-100M	100mm PVC-PVC	112 x 112mm	101mm	112mm		
	F1056-150M	150mm PVC-PVC	162 x 162mm	152mm	162mm		
F1056-225M	225mm PVC-PVC	252 x 252mm	240mm	256mm			
BLACK PVC PLUMBQWIK COUPLINGS							
FOR JOINING PVC TO PVC OR COMBINATIONS OF PVC, CAST IRON, COPPER AND GAL.- 20 TO 375mm DIAMETER							
	F1056-33	80mm PVC-PVC-Cu-Gal-Cl	89 x 89mm	75mm	92mm		
	F1056-100	25mm PVC-PVC-Cu-Gal-Cl	33 x 33mm	28mm	35mm		
	F1060-22	65mm PVC-PVC-Cu-Gal-Cl	20 x 70mm	53mm	71mm		
	F1056-075	20mm PVC-PVC-Cu-Gal-Cl	26 x 26mm	25mm	27mm		
	F1004-1010	300m PVC-PVC-Cu-Gal-Cl	323 x 323mm	299mm	317mm		
	F1056-1515	375mm PVC-PVC-Cu-Gal-Cl	391 x 391mm	368mm	400mm		
FOR JOINING EARTHENWARE TO PVC							
100 TO 225mm DIAMETER							
	F1006-100M	100mm EW-PVC	142 x 111mm	135mm	144mm	101mm	111mm
	F1006-150M	150mm EW-PVC	198 x 162mm	185mm	200mm	152mm	162mm
	F1006-225M	225mm EW-PVC	290 x 252mm	268mm	282mm	240mm	256mm
FOR JOINING EARTHENWARE TO PVC							
100 TO 225mm DIAMETER							
	F1006-43	100mm EW-80mm PVC	142 x 85mm	127mm	142mm	80mm	92mm
	F1006-64	150mm EW-100mm PVC	198 x 111mm	184mm	202mm	98mm	112mm
	F1002-1212	300mm EW-300mm PVC-Cu-Gal-Cl	365 x 320mm	349mm	373mm	298mm	321mm
	F1002-1515	375mm EW-375mm PVC-Cu-Gal-Cl	453 x 391mm	426mm	466mm	363mm	400mm
FOR JOINING/REDUCING PVC TO PVC							
40 TO 225mm DIAMETER							
	F1056-40/32M	40mmPVC-32mm PVC (Grey)	40 x 32mm	30mm	36mm	37mm	45mm
	F1056-215	50mm-40mm PVC	60 x 48mm	43mm	50mm	54mm	64mm
	F1056-50/40M	50mmPVC-40mm PVC (Grey)	50 x 40mm	37mm	45mm	50mm	58mm
	F1056-32	80mm-50mm PVC	85 x 60mm	56mm	62mm	75mm	92mm
	F1056-42	100mm-50mm PVC	111 x 60mm	56mm	62mm	102mm	116mm
	F1056-43	100mm-80mm PVC	111 x 85mm	76mm	92mm	102mm	118mm
	F1056-64	150mm-100mm PVC	162 x 111mm	104mm	116mm	160mm	171mm
	F1006-1212	375mm-300mm PVC	416 x 318mm	298mm	320mm	394mm	419mm
FOR JOINING EARTHENWARE TO EARTHENWARE							
100 TO 375mm DIAMETER							
	F1004-44	EW-EW	142 x 142mm	131mm	146mm		
	F1004-66	EW-EW	193 x 193mm	190mm	200mm		
	F1055-1010	EW-EW	282 x 282mm	265mm	282mm		
	F1001-1212	EW-EW	365 x 365mm	348mm	371mm		
	F1001-1515	EW-EW	453 x 453mm	414mm	462mm		

PRODUCT	CODE	DESCRIPTION & NOMINAL SIZE	ACTUAL SIZE	MIN	MAX	MIN	MAX
FOR JOINING EARTHENWARE TO PVC OR EARTHENWARE TO CAST IRON, COPPER AND GAL							
80 TO 375mm DIAMETER							
	F1006-43	100mm EW-80mm PVC	142 x 85mm	127mm	142mm	80mm	92mm
	F1006-64	150mm EW-100mm PVC	198 x 111mm	184mm	202mm	98mm	112mm
	F1004-86	150mm EW-225mm PVC	260 x 198mm	248mm	264mm	178mm	206mm
FOR JOINING AC, FRC OR CAST IRON TO PVC, CAST IRON AND GAL							
100 TO 300mm DIAMETER							
	F1051-44	100mm AC/CI/FRC-100mmPVC	120 x 111mm	115mm	125mm	102mm	115mm
	F1051-64	100mm AC/CI/Super Sleeve-150mm PVC	177 x 111mm	104mm	113mm	160mm	170mm
	F1051-66	150mm AC/CI/Super Sleeve-150mm PVC	177 x 162mm	164mm	178mm	149mm	164mm
	F1002-66	150mm FRC/Super Sleeve-150mm PVC	187 x 162mm	179mm	192mm	156mm	170mm
	F1006-1010	225mm AC,FRC Class1-300mm PVC	320 x 269mm	250mm	270mm	305mm	326mm
FOR JOINING AC/FRC TO AC/FRC							
100 TO 300mm DIAMETER							
	F1055-44	100mm AC-100mm AC	120 x 120mm	115mm	125mm		
	F1001-66	150mm FRC class1-150mm FRC-class1	191 x 191mm	180mm	193mm		
	F1055-66	150mm Super Sleeve-150mm Super Sleeve	180 x 180mm	161mm	179mm	161mm	179mm
	F1056-1010	225mm FRC-225 FRC class1-225 Super Sleeve	269 x 269mm	260mm	274mm		
QWIKCAP END CAP -RE-USABLE TESTING CAPS FOR SEALING LINES, AIR, SMOKE OR WATER TESTING							
	FQC-101	40mm PVC-Cu-Gal-CI	41-50mm	40mm PVC-Cu-Gal-CI			
	FQC-102	50mm PVC-Cu-Gal-CI	49-63mm	50mm PVC-Cu-Gal-CI			
	FQC-103	80mm PVC-Cu-Gal-CI	79-92mm	80mm PVC-Cu-Gal-CI			
	FQC-104	100mm PVC-Cu-Gal-CI	101-117mm	100mm PVC-Cu-Gal-CI			
	FQC-105	125mm PVC-Cu-Gal-CI	128-149mm	100mm EW			
	FQC-106	150mm PVC-Cu-Gal-CI	146-168mm	150mm PVC-Cu-Gal-CI			
EXPANSION JOINTS FOR VERTICAL INSTALLATIONS SUIT 50MM AND 100MM PVC OR GALV, CAST IRON, COPPER							
	FXJ-2	50mm PVC - PVC-Cu-Gal-CI	50-57mm	50mm PVC			
	FXJ-4	100mm PVC - PVC-Cu-Gal-CI	100-112mm	100mm PVC			
DISHWASHER DRAIN CONNECTOR							
	FDWC-100		20mm	25mm	28mm	20mm	28mm
DRAIN TAP CONNECTOR							
	FDTC-150			32mm	38mm	44mm	50mm
	FDTC-215			32mm	38mm	54mm	63mm

SHEAR RINGS IN 316 STAINLESS STEEL ADD STRENGTH AND RIGIDITY TO STANDARD COUPLINGS

	FSR-19	Will suit 100mm PVC 50mm wide SS 316	111mm x 50mm	100mm PVC x 50mm wide
	FSR-27	Will suit 150mm FRC 100mm wide SS 316	162mm x 100mm	150mm PVC x 100mm wide
	FSR-28	Will suit 150mm EW 100mm wide SS 316	198mm x 100mm	150mm EW x 100mm wide

WASHING MACHINE HOSE GRIP CONNECTOR, CLAMPS TO 50MM DWV SECURES WASHING MACHINE DRAIN HOSE

	FHG-1		57mm	50mm PVC
---	-------	--	------	----------

TORQUE WRENCH TO SUIT HEX HEAD HOSE CLAMP SCREWS

	FTW-100		5/16"	N/A
--	---------	--	-------	-----

QWIK ACCESS

A secure, removable and pre-assembled point of entry into 80-150mm diameter plastic, ductile and cast iron pipes.

- For entry into drainage systems where no inspection point exists.
- Quick and easy
- Withstands up to 1 bar
- Can be removed and re-fitted
- Pre-assembled for direct insertion into the host pipe

FQA Single Qwik Access point 54mm
 FQA-Kit Kit includes
 10 x 54mm Qwik Access points, 1 x De Burring Tool, 1 x 6mm Allen Key, 1 x 54mm Diamond Core Drill bit.



FLEXIBLE BOSS JUNCTION (Saddle)

A fast and cost effective way to connect a stormwater pipe into a new or existing line

- Manufactured from a specially formulated flexible PVC membrane.
- Rigid, yet flexible enough for one saddle to fit 150mm or larger stormwater mains.
- Includes special "slip-lock" quick-adjust stainless steel clamps allowing fast and simple installations into stormwater mains
- Larger apron with locating ring provides a positive and effective seal.
- Suitable for most stormwater pipe diameters, over 150mm.
- Leak-proof, resistant to chemicals, ultraviolet rays, fungal growth and normal sewer gases.

FTSW-4 45° Flexible Boss Junction 100mm
 FTSW-6 45° Flexible Boss Junction 150mm
 FTST-4 90° Flexible Boss Junction 100mm
 FTST-6 90° Flexible Boss Junction 150mm

