



1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND SUPPLIER

PRODUCT NAME: GENERAL PURPOSE CEMENT (PORTLAND CEMENT)
RECOMMENDED USE AS IS USED AS A BINDER IN CONCRETE, CONCRETE MASONRY, MORTAR AND GROUTS. IT IS ALSO USED IN THE MANUFACTURE OF FIBRE CEMENT PRODUCTS, IN SOIL STABILISATION IN BUILDING CONSTRUCTION AND CIVIL ENGINEERING PROJECTS.
SUPPLIER CEMIX LIMITED
ADDRESS 19 ALFRED STREET ONEHUNGA, AUCKLAND, NEW ZEALAND.
TELEPHONE 64 9 636 1000
FACSIMILE 64 9 636 0000
EMERGENCY CONTACT 0800 ASK CEMIX

2. HAZARDS IDENTIFICATION

HAZARD CATEGORY Hazardous substance (Hazardous substances regulations 2001).
Non-dangerous good.

RISK PHRASES

6.3A SKIN IRRITANT
6.9B TARGET ORGANIC TOXICANT
8.3A EYE CORROSIVE

SAFETY PHRASES

S24- AVOID CONTACT WITH SKIN
S 25 -AVOID CONTACT WITH EYES
S36- WEAR SUITABLE PROTECTIVE CLOTHING
S37- WEAR SUITABLE GLOVES
S39- WEAR EYE / FACE PROTECTION.

HAZARD STATEMENTS:

H315 IRRITATING IN CONTACT WITH SKIN. REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING. MAY CAUSE SENSITISATION BY SKIN CONTACT.
H363 HARMFUL BY INHALATION AND IF SWALLOWED.
H318 IRRITATING TO EYES

3. COMPOSITION / INFORMATION ON INGREDIENTS

PORTLAND CEMENT CONSISTS OF A CRYSTALLINE MASS MANUFACTURED FROM SUBSTANCES MINED FROM THE EARTH'S CRUST. IT CONTAINS TRACE AMOUNTS OF NATURALLY OCCURRING, BUT POTENTIALLY HAZARDOUS CHEMICAL ENTITIES INCLUDING

The above info is based on our best knowledge and we believe it to be true and correct. However due to the variable nature of application, the suitability of the product for the use intended is the sole responsibility of the user

CEMIX LIMITED 19 Alfred Street Onehunga, Auckland, New Zealand.

Tel: 09-636-1000. Fax: 09-636-0000. Helpline: 0800 ASK CEMIX. Email: info@cemix.co.nz Website: www.cemix.co.nz

Date of Issue: 13/11/2013

Issue: 2

Ref: SDS 31



METALS SUCH AS CHROMIUM AND NICKEL, CRYSTALLINE SILICA, POTASSIUM SULPHATE, CALCIUM / MAGNESIUM OXIDES AND NICKEL COMPOUNDS. ALL SIGNIFICANT CONSTITUENTS ARE LISTED BELOW:

CHEMICAL IDENTITY	CAS NUMBER	PROPORTION
Portland Cement Clinker	65997-15-1	<97%
3CaO.SiO ₂	12168-85-3	
2CaO.SiO ₂	1344-95-2	
3CaO.Al ₂ O ₃	12042-78-3	
4CaO.Al ₂ O ₃ .Fe ₂ O ₃	12068-35-8	
Crystalline Quartz	14808-60-7	<1%
Hexavalent Chrome (Cr VI)	18540-29-9	<20ppm
Gypsum (CaSO ₄ .2H ₂ O)	13397-24-5	2-5%
Calcium Oxide (CaO)	1305-78-8	1-3%
NONE HAZARDOUS INGREDIENTS:		4 - 5 %

4. FIRST AID

EYE : FLUSH THOROUGHLY WITH FLOWING WATER FOR 15 MINUTES TO REMOVE ALL TRACES. IF SYMPTOMS SUCH AS IRRITATION OR REDNESS PERSIST, SEEK MEDICAL ATTENTION. IF WET CEMENT IS SPLASHED IN THE EYE, ALWAYS TREAT AS ABOVE, AND SEEK URGENT MEDICAL ATTENTION.

SKIN : REMOVE HEAVILY CONTAMINATED CLOTHING IMMEDIATELY. WASH OFF SKIN THOROUGHLY WITH WATER. USE A MILD SOAP IF AVAILABLE. SHOWER IF NECESSARY. SEEK MEDICAL ATTENTION FOR PERSISTENT IRRITATION OR BURNING OF THE SKIN. MUCOUS MEMBRANES OF THE RESPIRATORY TRACT. SEEK MEDICAL ATTENTION IF IRRITATION OCCURS

SWALLOWED: RINSE MOUTH AND LIPS WITH WATER. DO NOT INDUCE VOMITING. GIVE WATER TO DRINK TO DILUTE STOMACH CONTENTS. IF SYMPTOMS PERSIST, SEEK MEDICAL ATTENTION.

INHALED: REMOVE TO FRESH AIR, AWAY FROM DUSTY AREA. IF SYMPTOMS PERSIST, SEEK MEDICAL ATTENTION.

FIRST AID FACILITIES: EYE WASH STATION. WASHING FACILITIES WITH RUNNING WATER.

ADVICE TO DOCTOR: FOR ADVICE CONTACT THE NATIONAL POISONS CENTRE 0800 POISON

The above info is based on our best knowledge and we believe it to be true and correct. However due to the variable nature of application, the suitability of the product for the use intended is the sole responsibility of the user

CEMIX LIMITED 19 Alfred Street Onehunga, Auckland, New Zealand.

Tel: 09-636-1000. Fax: 09-636-0000. Helpline: 0800 ASK CEMIX. Email: info@cemix.co.nz Website: www.cemix.co.nz

Date of Issue: 13/11/2013

Issue: 2

Ref: SDS 31



(0800 764 766) OR A DOCTOR. TREAT SYMPTOMATICALLY. WET CEMENT BURNS TO SKIN OR EYE MAY RESULT IN CORROSIVE CAUSTIC BURNS. INGESTION OF SIGNIFICANT AMOUNTS OF CEMENT DRY OR WET IS UNLIKELY. DO NOT INDUCE EMESIS OR PERFORM GASTRIC LAVAGE. NEUTRALIZATION WITH ACIDIC AGENTS IS NOT ADVISED BECAUSE OF INCREASED RISKS OF EXOTHERMIC BURNS. WATER-MINERAL OIL SOAKS MAY AID IN REMOVING HARDENED CEMENT FROM THE SKIN. OPHTHALMOLOGICAL OPINION SHOULD BE SOUGHT FOR OCULAR BURNS.

5. FIRE FIGHTING MEASURES

FIRE/EXPLOSION HAZARD: NONE
FLAMMABILITY: NOT FLAMMABLE
EXTINGUISHING MEDIA: NONE REQUIRED
HAZARDS FROM COMBUSTION PRODUCTS: NONE
SPECIAL PROTECTIVE PRECAUTIONS: None required

6. ACCIDENTAL RELEASE MEASURES

SPILLS: SPILLS ARE BEST CLEANED UP BY VACUUM DEVICE TO AVOID GENERATING AIRBORNE DUST. RECOMMENDATIONS ON EXPOSURE CONTROL AND PERSONAL PROTECTION SHOULD BE FOLLOWED DURING SPILL CLEAN UP. KEEP PRODUCT OUT OF STORM WATER AND SEWER DRAINS. WETTING DURING CLEAN UP WILL CAUSE FORMATION OF SETTING CEMENT.

7. HANDLING AND STORAGE

PRECAUTIONS: DO NOT BREATHE DUST. WEAR PROTECTIVE GLOVES, EYE AND FACE PROTECTION.

HANDLING: WHEN SUPPLIED IN BAGS THESE NEED TO BE HANDLED IN ACCORDANCE WITH MANUAL HANDLING REGULATIONS AND CODE OF PRACTICE. AVOID CONTACT WITH EYES. WEAR EYE PROTECTION. AVOID SKIN CONTACT AND INHALATION. WASH EXPOSED SKIN THOROUGHLY AFTER HANDLING.

STORAGE: PROTECT FROM MOISTURE TO PREVENT HARDENING. STORAGE OF CEMENT MAY BE IN CONCRETE SILOS, STEEL BINS, OR PLASTIC LINED MULTI-WALL PAPER BAGS. ENSURE PACKAGES ARE ADEQUATELY LABELED, SEALED AND PROTECTED FROM PHYSICAL DAMAGE. STORE IN COOL, DRY, WELL-VENTILATED AREA. AVOID CONTACT WITH OXIDISING AGENTS, ACIDS, ETHANOL AND HALOGENS.

The above info is based on our best knowledge and we believe it to be true and correct. However due to the variable nature of application, the suitability of the product for the use intended is the sole responsibility of the user

CEMIX LIMITED 19 Alfred Street Onehunga, Auckland, New Zealand.

Tel: 09-636-1000. Fax: 09-636-0000. Helpline: 0800 ASK CEMIX. Email: info@cemix.co.nz Website: www.cemix.co.nz

Date of Issue: 13/11/2013

Issue: 2

Ref: SDS 31



8.EXPOSURE CONTROLS AND PERSONAL PROTECTION

EXPOSURE LIMITS: EXPOSURE TO DUST SHOULD BE KEPT AS LOW AS PRACTICABLE, AND BELOW THE FOLLOWING LEVELS:

PORTLAND CEMENT: 10MG/M3 TWA (TIME-WEIGHTED AVERAGE) AS INSPIRABLE DUST.

CRYSTALLINE SILICA (QUARTZ): 0.1 MG/M3 TWA AS RESPIRABLE DUST (7 MICRONS PARTICLE EQUIVALENT AERODYNAMIC DIAMETER).

CHROMIUM VI (HEXAVALENT): 0.05 MG/M3.

OUTSIDE WORKPLACE EXPOSURE LIMITS:

NO TEL OR EEL IS SET FOR THIS SUBSTANCE AT THIS TIME.

ENGINEERING CONTROLS: ALL WORK WITH DRY CEMENT SHOULD BE CARRIED OUT IN SUCH A WAY AS TO MINIMISE DUST GENERATION, EXPOSURE TO DUST AND REPEATED OR EXTENDED SKIN CONTACT. WHEN HANDLING DRY CEMENT, USE LOCAL MECHANICAL VENTILATION OR EXTRACTION IN AREAS WHERE DUST COULD ESCAPE INTO THE WORK ENVIRONMENT. FOR BULK DELIVERIES, CLOSED PUMPING SYSTEMS ARE RECOMMENDED. FOR HANDLING OF INDIVIDUAL BAGS, FOLLOW INSTRUCTIONS BELOW IF NO LOCAL EXHAUST VENTILATION IS AVAILABLE. LOCAL DUST EXTRACTION AND COLLECTION MAY BE USED, IF NECESSARY, TO CONTROL AIRBORNE DUST LEVELS. WORK METHODS AND ENGINEERING SHOULD AIM TO MINIMISE CONTACT WITH WET CEMENT ONTO EXPOSED SKIN. WORK AREAS SHOULD BE CLEANED REGULARLY.

SKIN PROTECTION:

MINIMISE CONTACT WITH PORTLAND CEMENT MATERIALS. WHEN HANDLING DRY OR WET CEMENT, WET CONCRETE, MORTAR OR GROUT, PERSONNEL SHOULD WEAR PROTECTIVE CLOTHING AND IMPERVIOUS FOOTWEAR, AND GLOVES SUCH AS PVC (SEE AUSTRALIAN AND NEW ZEALAND STANDARDS AS/NZS 4501 AND AS 2161). NEVER KNEEL IN WET CEMENT, OR ALLOW EXTENDED CONTACT OF SKIN WITH WET CEMENT. REMOVE CLOTHING WHICH HAS BECOME CONTAMINATED WITH WET OR DRY CEMENT TO AVOID PROLONGED CONTACT WITH THE SKIN. IF CEMENT GETS INTO BOOTS, REMOVE SOCKS AND BOOTS IMMEDIATELY AND WASH SKIN THOROUGHLY. WASH WORK CLOTHES REGULARLY. TO AVOID CONTAMINATION OF FACE AND LIPS AND INGESTION, WASH HANDS BEFORE EATING OR SMOKING.

EYE PROTECTION: SPLASH RESISTANT SAFETY GLASSES WITH SIDE SHIELDS OR SAFETY GOGGLES (AS/NZ 1336) OR A FACE SHIELD SHOULD BE WORN TO ENSURE ALL CONTACT WITH EYES IS AVOIDED.

The above info is based on our best knowledge and we believe it to be true and correct. However due to the variable nature of application, the suitability of the product for the use intended is the sole responsibility of the user

CEMIX LIMITED 19 Alfred Street Onehunga, Auckland, New Zealand.

Tel: 09-636-1000. Fax: 09-636-0000. Helpline: 0800 ASK CEMIX. Email: info@cemix.co.nz Website: www.cemix.co.nz

Date of Issue:13/11/2013

Issue: 2

Ref: SDS 31



RESPIRATORY PROTECTION: WHERE ENGINEERING AND HANDLING CONTROLS ARE NOT ADEQUATE TO MINIMISE EXPOSURE TO TOTAL DUST AND TO RESPIRABLE CRYSTALLINE SILICA WEAR A SUITABLE P1 OR P2 PARTICULATE RESPIRATOR (AS/NZS 1715 AND AS/NZS 1716). USE ONLY RESPIRATORS THAT BEAR THE NEW ZEALAND STANDARDS MARK AND ARE FITTED AND MAINTAINED CORRECTLY. FOR DUST LEVELS APPROACHING OR EXCEEDING THE NES (SEE ABOVE) A MORE EFFECTIVE PARTICULATE RESPIRATOR AS DESCRIBED IN AS/NZS 1715 SHOULD BE WORN. PROCEDURES FOR EFFECTIVE USE OF RESPIRATORS SHOULD BE APPLIED AND SUPERVISED.

ENGINEERING CONTROLS: ENSURE EFFECTIVE VENTILATION TO CONTROL THE CONTAMINATION OF AIR.

PERSONAL PROTECTION : WEAR FULL OVERALLS, GLOVES AND SAFETY GOGGLES WHEN HANDLING THE PRODUCT. AVOID SKIN AND EYE CONTACT AS WELL AS INHALATION.. ALWAYS WASH HANDS BEFORE EATING, DRINKING, SMOKING OR USING THE TOILET. WASH ANY CONTAMINATED CLOTHING OR PROTECTIVE EQUIPMENT BEFORE REUSE OR STORAGE

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: A FINE GREY POWDER
ODOUR: NO DISTINCTIVE ODOUR
BOILING/MELTING POINT: MELTING POINT >1200OC
VAPOUR PRESSURE: NOT APPLICABLE
SPECIFIC GRAVITY: 3.0 – 3.2
FLASH POINT: NOT APPLICABLE
FLAMMABILITY LIMITS: NOT APPLICABLE
SOLUBILITY IN WATER: SLIGHT, REACTS ON MIXING WITH WATER FORMING AN ALKALINE (CAUSTIC) SOLUTION (PH >11)
PARTICLE SIZE: UP TO 50% OF THE FRESH DRY MATERIAL MAY BE RESPIRABLE (BELOW 10 MICRONS)

10. STABILITY

CHEMICAL STABILITY: CHEMICALLY STABLE
CONDITIONS TO AVOID: KEEP FREE OF MOISTURE
INCOMPATIBLE MATERIALS: NONE
HAZARDOUS DECOMPOSITION PRODUCTS: NONE
HAZARDOUS REACTIONS: NONE

11. TOXICOLOGICAL INFORMATION

The above info is based on our best knowledge and we believe it to be true and correct. However due to the variable nature of application, the suitability of the product for the use intended is the sole responsibility of the user

CEMIX LIMITED 19 Alfred Street Onehunga, Auckland, New Zealand.

Tel: 09-636-1000. Fax: 09-636-0000. Helpline: 0800 ASK CEMIX. Email: info@cemix.co.nz Website: www.cemix.co.nz

Date of Issue: 13/11/2013

Issue: 2

Ref: SDS 31



PORTLAND CEMENTS ARE STABLE SUBSTANCES, COMPATIBLE WITH MOST OTHER BUILDING MATERIALS, WILL NOT DECOMPOSE INTO HAZARDOUS BY-PRODUCTS AND DO NOT POLYMERISE.

SHORT TERM (ACUTE) EXPOSURE

SWALLOWED: UNLIKELY UNDER NORMAL INDUSTRIAL USE. MILDLY ABRASIVE AND CORROSIVE TO MOUTH AND THROAT IF SWALLOWED. MAY CAUSE NAUSEA, STOMACH CRAMPS AND CONSTIPATION.

EYES: IRRITATING AND CORROSIVE TO THE EYES AND MAY CAUSE ALKALINE BURNS. CEMENT DUST IS IRRITATING TO THE EYES. EXPOSURE TO DUST MAY AGGRAVATE EXISTING EYE IRRITATIONS.

SKIN: DUST IS IRRITATING AND DRYING TO THE SKIN. DIRECT CONTACT WITH WET CEMENT MAY CAUSE SERIOUS SKIN BURNS. WITHIN 12 TO 48 HOURS (AFTER ONE- TO SIX-HOUR EXPOSURES) POSSIBLE FIRST, SECOND OR THIRD DEGREE BURNS MAY OCCUR. THERE MAY BE NO OBVIOUS PAIN AT THE TIME OF THE EXPOSURE. CHRONIC SKIN DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO DUST OR CONTACT WITH WET CEMENT.

INHALED: CEMENT DUST IS IRRITATING TO THE NOSE, THROAT AND RESPIRATORY TRACT CAUSING COUGHING AND SNEEZING. PRE-EXISTING UPPER RESPIRATORY AND LUNG DISEASES INCLUDING ASTHMA AND BRONCHITIS MAY BE AGGRAVATED.

LONG TERM (CHRONIC) EXPOSURE

EYES: DUST MAY CAUSE IRRITATION AND INFLAMMATION OF THE CORNEA.

SKIN: REPEATED CONTACT CAUSES IRRITATION AND DRYING OF THE SKIN AND CAN RESULT IN SKIN REDDENING AND SKIN RASH (DERMATITIS). OVER TIME THIS MAY BECOME CHRONIC AND CAN ALSO BECOME INFECTED. PERSONS WHO ARE ALLERGIC TO CHROMIUM MAY DEVELOP AN ALLERGIC DERMATITIS WHICH AGGRAVATES THE IRRITANT EFFECTS AND THIS COMBINATION CAN LEAD TO CHRONIC CEMENT DERMATITIS AND SERIOUS DISABILITY PARTICULARLY AFFECTING THE HANDS.

INHALED: REPEATED EXPOSURE TO THE DUST MAY RESULT IN INCREASED NASAL AND RESPIRATORY SECRETIONS AND COUGHING. INFLAMMATION OF LINING TISSUE OF THE RESPIRATORY SYSTEM MAY FOLLOW REPEATED EXPOSURE TO HIGH LEVELS OF DUST, WITH INCREASED RISK OF BRONCHITIS AND PNEUMONIA.

REPEATED AND PROLONGED EXPOSURE TO DUST LEVELS WHICH EXCEED THE OES FOR

The above info is based on our best knowledge and we believe it to be true and correct. However due to the variable nature of application, the suitability of the product for the use intended is the sole responsibility of the user

CEMIX LIMITED 19 Alfred Street Onehunga, Auckland, New Zealand.

Tel: 09-636-1000. Fax: 09-636-0000. Helpline: 0800 ASK CEMIX. Email: info@cemix.co.nz Website: www.cemix.co.nz

Date of Issue: 13/11/2013

Issue: 2

Ref: SDS 31



CRYSTALLINE SILICA (SEE ABOVE) MAY OCCUR. THIS CAN CAUSE BRONCHITIS, AND SILICOSIS (SCARRING OF THE LUNG). LONG TERM OVEREXPOSURE TO RESPIRABLE CRYSTALLINE SILICA DUST MAY INCREASE THE RISK OF OTHER IRREVERSIBLE AND SERIOUS DISORDERS INCLUDING SCLERODERMA (A DISEASE AFFECTING THE CONNECTIVE TISSUE OF THE SKIN, JOINTS, BLOOD VESSELS AND INTERNAL ORGANS).

CEMENT (PORTLAND CEMENT) IS NOT CLASSIFIED AS A CARCINOGEN BY NOHSC. OF THE INGREDIENTS HEXAVALENT CHROMIUM (CR VI) IS CLASSIFIED AS A CARCINOGEN BY NOHSC. THERE IS DEBATE IN THE MEDICAL LITERATURE CONCERNING WHETHER THERE IS ANY RISK OF LUNG CANCER ARISING FROM LONG TERM HIGH OVER EXPOSURE TO RESPIRABLE CRYSTALLINE SILICA. RISK OF LUNG CANCER HAS NOT BEEN IDENTIFIED FROM USING PORTLAND CEMENTS CONTAINING SILICA. THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS CLASSIFIED CRYSTALLINE SILICA, INHALED IN THE FORM OF QUARTZ OR CRISTOBALITE FROM OCCUPATIONAL SOURCES, AS CARCINOGENIC TO HUMANS (GROUP 1). NOHSC HAS NOT CLASSIFIED CRYSTALLINE SILICA AS A CARCINOGEN.

12. ECOLOGICAL INFORMATION

CLASSIFIED AS AN AQUATIC ECOTOXIC UNDER THE HAZARDOUS SUBSTANCES AND NEW ORGANISMS ACT. CLASSIFIED AS NON-TOXIC IN SOILS OR TO TERRESTRIAL VERTEBRATES / INVERTEBRATES

ECOTOXICITY: PRODUCT FORMS AN ALKALINE SLURRY WHEN MIXED WITH WATER.

PERSISTENCE AND DEGRADABILITY: PRODUCT IS PERSISTENT AND WOULD HAVE A LOW DEGRADABILITY.

MOBILITY: A LOW MOBILITY WOULD BE EXPECTED IN A LANDFILL SITUATION.

13. DISPOSAL CONSIDERATIONS

PORTLAND CEMENT CAN BE TREATED AS A COMMON WASTE FOR DISPOSAL OR DUMPED INTO A LANDFILL SITE, IN ACCORDANCE WITH LOCAL AUTHORITY GUIDELINES. KEEP MATERIAL OUT OF STORM WATER AND SEWER DRAINS. MEASURES SHOULD BE TAKEN TO PREVENT DUST GENERATION DURING DISPOSAL, AND EXPOSURE AND PERSONAL PRECAUTIONS SHOULD BE OBSERVED (SEE ABOVE).

14. TRANSPORT INFORMATION IS NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE DANGEROUS GOODS CODE FOR TRANSPORT BY ROAD AND RAIL.

The above info is based on our best knowledge and we believe it to be true and correct. However due to the variable nature of application, the suitability of the product for the use intended is the sole responsibility of the user

CEMIX LIMITED 19 Alfred Street Onehunga, Auckland, New Zealand.

Tel: 09-636-1000. Fax: 09-636-0000. Helpline: 0800 ASK CEMIX. Email: info@cemix.co.nz Website: www.cemix.co.nz

Date of Issue: 13/11/2013

Issue: 2

Ref: SDS 31



15. REGULATORY INFORMATION

POISON SCHEDULE : NOT SCHEDULED

16. OTHER INFORMATION

DATE OF PREPARATION : 12TH NOVEMBER 2013

DATE OF REVISION 12TH NOVEMBER 2015

REASON FOR ISSUE :THIS DATA SHEET AND THE HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION IT CONTAINS HAS BEEN PREPARED BY CEMIX LTD ACCORDING TO CURRENT REGULATORY REQUIREMENTS AS AT DATE OF ISSUE. THE PRECAUTIONS AND ADVICE PROVIDED MAY NOT BE ACCURATE FOR ALL INDIVIDUALS AND/OR SITUATIONS. IT IS THE USER'S OBLIGATION TO EVALUATE AND USE THIS PRODUCT SAFELY AND COMPLY WITH ALL APPLICABLE LEGISLATION.

•

The above info is based on our best knowledge and we believe it to be true and correct. However due to the variable nature of application, the suitability of the product for the use intended is the sole responsibility of the user

CEMIX LIMITED 19 Alfred Street Onehunga, Auckland, New Zealand.

Tel: 09-636-1000. Fax: 09-636-0000. Helpline: 0800 ASK CEMIX. Email: info@cemix.co.nz Website: www.cemix.co.nz

Date of Issue:13/11/2013

Issue: 2

Ref: SDS 31