

## DATA SHEET

# BITUPATCH™

## BTP020



### DESCRIPTION

Ready to use, no mixing required Bitumen cold mix asphalt for the repair of potholes in roads, driveways and paths.

### RECOMMENDED USE

It is generally used for:

- Potholes in asphalt
- Repairs deteriorating asphalt
- Speed humps
- Ramps
- Water channels

### PACKAGING

20kg bags weather resistant foil bags

### YIELD

One 20kg bag will produce asphalt approximately equivalent to 0.0018m<sup>3</sup>. (500m x 500mm x 30mm)

### DIRECTIONS FOR USE

1. **Clean** the hole of any debris and remove any loose pieces around the hole (and if possible give yourself a vertical edge around the hole for the Bitupatch to butt up against - it lengthens the life of the repair)
2. **Fill** the hole with Bitupatch (make middle slightly higher than the sides - this is called crowning - depending on the size of the repair give yourself a 5-10 crown - this counteracts the subsidence caused by compacting). Bitupatch is ready to use straight from the bag, no mixing required.
3. **Compact** (a compactor is recommended for larger holes while driving back and forth over it in a vehicle or timber posts (eg 100mm x 100mm) can be used on smaller holes very effectively)

*NB/ for sealing your pothole around the edges we recommend you use Bitupatch Crackfix to prevent water getting back in destabilising the sub-base*

### STORAGE

Sealed bags have a shelf life of 12 months if stored in a cool environment.

### WARNINGS SAFETY

Avoid contact with eyes and skin. Wear suitable protective clothing, gloves, eye protection and barrier cream. Wash thoroughly after handling and properly store any leftover material.

### FIRST AID

Irrigate eyes with plenty of water and seek medical advice immediately.

### SPILLS AND LEAKS

Keep out of sewers and storm water drains and dispose of any leftover material as trade waste in accordance with local authority guidelines.

Additional information can be had from the brochures or by calling 0800 ASK CEMIX

### DISCLAIMER

*Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX LTD does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of CEMIX LTD. If you need advice concerning the use of suitability of this product for your particular application, please contact CEMIX LTD first. If this product is defective because of CEMIX LTD's fault, please contact the supplier or CEMIX LTD. who will replace it at no cost.*