## ♣ Cosmo Care Connector Suite

4.5/3 litre Plastic Cistern, Connector Toilet Suite.

Dual Flush Toilet Suite for accessible application installations complying to the WC pan requirements to AS 1428.1-2009.

A contemporary designed 4.5/3 litre dual flush **Cosmo Care** toilet suite installation designed to provide a raised seat height of between 460-480mm for accessible applications **b**. The pan features a concealed trap which facilitates easy cleaning. The versatility of the **Cosmo Care Pan** with concealed trap makes it ideal for use by both the ambulant person with disabilities and wheel-chair users

including wheeled commode chairs.

Important: Further reference must be made to AS 1428.1-2009 with current amendments to determine circulation space, grabrail and installation requirements. The dimensions in this sheet may change with amendments to the standard.

Pan: Cosmo Care Pan with concealed trap, 4.5 litre full flush washdown type.

**Traps:** S trap (WELS 4 star rated) or P trap (WELS 3 star rated). Unvented only.

Inlet: 50mm back inlet.

Cistern: Cosmo Cistern – A one piece injection moulded tank with a removable lid and centrally positioned Caroma Care plastic push buttons. The inlet valve is the Quietflow 2 inlet valve which reduces noise during the filling cycle.

Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant.

**Inlet and Overflow:** Inlet is in the RH position and is located on the underside of the cistern and is interchangeable. Overflow is internal as standard, an external overflow kit is available.

Position of the Pan: For wheel chair access the installed pan must be  $800 \pm 10$ mm from the front of the pan to the finished wall and provide a seat height of 460 to 480mm. The projection requirements for people with ambulant disabilities that is suitable for this suite is 625 to 660mm.


**Position of the Cistern:** The underside of the cistern must be 600mm minimum from the finished floor. The push button height should be no greater than 1100mm from the finished floor.

Seats: Recommended Caroma seats - Caravelle Care single or double flap (refer to SEATS section for colour options and further details).

**Installation:** Refer to *Important Information for Plumbers* section. **Colours:** White only.



## & Cosmo Care Connector Suite (continued)



Note: The projection requirements detail on this illustration are for wheel chair access only. The projection requirements for people with ambulant disabilities that is suitable for this suite is 625 to 660mm.

For height dimensions to underside of pan, make allowance for mortar bedding.