

# **Safety Data Sheet**

© 2016, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:33-8536-6Version number:1.00Issue Date:28/11/2016Supersedes date:Initial issue.

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances and New Organisms Act 1996 (HSNO Act) and Regulations, as amended.

# **SECTION 1: Identification**

#### 1.1. Product identifier

Scotchgard™ Heavy Duty Water Shield (Cat. No. 5020-10, 5020-10C, 5020-13)

#### **Product Identification Numbers**

70-0052-8367-9

#### 1.2. Recommended use and restrictions on use

# Recommended use

Repellent

#### 1.3. Supplier's details

Address: 3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland

**Telephone:** (09) 477 4040

E Mail: innovation@nz.mmm.com

Website: 3m.co.nz

#### 1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

# **SECTION 2: Hazard identification**

#### 2.1. Classification of the substance or mixture

Classified as hazardous according to the New Zealand, Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001 as amended.

Classified as a Dangerous Good according to; New Zealand, Land Transport Rule: Dangerous Goods 2005 (Rule 45001/1) as amended, NZS 5433:2012 Transport of Dangerous Goods on Land, UN Model Regulations on the Transport of Dangerous Goods, International Maritime Dangerous Goods Code and IATA Dangerous Goods Regulations. For transport classification, refer to SECTION 14: Transport Information.

#### **HSNO** classification

2.1.2A Flammable aerosol

6.1E Acute toxicity

6.3B Irritating to the skin

6.9A Toxic to human target organs/systems

# 9.4B Terrestrial invertebrate toxicity

# 2.2. Label elements SIGNAL WORD

DANGER!

#### **Symbols:**

Flame | Health Hazard | Environment |

#### **Pictograms**







### **HAZARD STATEMENTS:**

H222 Extremely flammable aerosol.

H313 May be harmful in contact with skin.

H316 Causes mild skin irritation.

H370 Causes damage to organs:

cardiovascular system

H442 Toxic to terrestrial invertebrates.

#### PRECAUTIONARY STATEMENTS

General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

**Prevention:** 

P104 Read Safety Data Sheet before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

**Response:** 

P332 + P313 If skin irritation occurs: Get medical advice/attention.
P307 + P311 IF exposed: Call a POISON CENTER or doctor/physician.
P312 Call a POISON CENTRE or doctor/physician if you feel unwell.

P391 Collect spillage.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50oC.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

#### 2.3. Other hazards

Contains gas under pressure; may explode if heated.

May cause drowsiness or dizziness.

# **SECTION 3: Composition/information on ingredients**

Ingredient	CAS Nbr	% by Weight
Hydrotreated Light Petroleum Distillates	64742-47-8	65 - 75
Petroleum Gases, Liquified, Sweetened	68476-86-8	23 - 27
Silicone Mixture	Trade Secret	2 - 6
Proprietary Resin	Trade Secret	1 - 4

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. Get medical attention.

#### Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

### 4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

# **SECTION 5: Fire-fighting measures**

# 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

#### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

# **Hazardous Decomposition or By-Products**

Substance	<b>Condition</b>
Formaldehyde	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Toxic vapour, gas, particulate.	During combustion.

## 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

\_\_\_\_\_

**5.4. Hazchem code:** 2YE

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

# **SECTION 7: Handling and storage**

Refer to Section 15: HSNO Controls for more information.

#### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

# 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Protect from sunlight. Store in a well-ventilated place. Store away from heat. Store away from acids. Store away from oxidising agents. Store away from areas where product may come into contact with food or pharmaceuticals.

#### 7.3. Approved handler test certificate

Class 2, required when present in quantities greater than 3,000 L (aggregate water capacity)

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

# Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

IngredientCAS NbrAgencyLimit typeAdditional commentsKerosine (petroleum)64742-47-8ACGIHTWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3A3: Confirmed animal carcin., SKIN

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines New Zealand WES: New Zealand Workplace Exposure Standards.

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit ppm: parts per million mg/m³: milligrams per cubic metre

CEIL: Ceiling

#### 8.2. Exposure controls

# 8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Indirect vented goggles.

Refer AS/NZS 1336 - Recommended practices for occupational eye protection and for performance specifications AS/NZS 1337, Parts 1 - 6 - Personal eye-protection.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Nitrile rubber.

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state Liquid.: Aerosol

**Specific Physical Form:** Aerosol

**Appearance/Odour** Colourless liquid with faint petroleum hydrocarbon odour.

Odour thresholdNo data available.pHNot applicable.Melting point/Freezing pointNot applicable.

**Boiling point/Initial boiling point/Boiling range** 174 °C

Flash point 39.4 °C [Test Method: Closed Cup] [Details: Liquid only;

propellent flash point <0 F]

**Evaporation rate**No data available.

Flammability (solid, gas)

Not applicable.

Flammable Limits(LEL)

Flammable Limits(UEL)

6 %

**Vapour pressure** 146.7 Pa [@ 20 °C ]

Vapour density 4.8 [Ref Std: AIR=1] [Details: Conditions: for CAS 64742-47-8]

**Density** 0.76 g/cm3

**Relative density** 0.76 [*Ref Std*:WATER=1]

Water solubilityNegligibleSolubility- non-waterNo data available.Partition coefficient: n-octanol/waterNo data available.

**Autoignition temperature** 230 °C - 315.6 °C [Details: Conditions: for CAS 64742-47-8]

**Decomposition temperature**No data available.

Viscosity1 mPa-sVolatile organic compounds (VOC)91.8 % weightVOC less H2O & exempt solvents697 g/l

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

#### 10.2 Chemical stability

Stable.

## 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

# 10.4 Conditions to avoid

Heat.

#### 10.5 Incompatible materials

Strong oxidising agents.

#### 10.6 Hazardous decomposition products

<u>Substance</u> <u>Condition</u>

None known.

Refer to Section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

#### Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Intentional concentration and inhalation may be harmful or fatal. Simple asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

May be harmful in contact with skin.

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

#### Eve contact

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### **Additional Health Effects:**

#### Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Single exposure, above recommended guidelines, may cause:

Cardiac sensitisation: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE2,000 - 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrotreated Light Petroleum Distillates	Dermal	Rabbit	LD50 > 3,160 mg/kg
Hydrotreated Light Petroleum Distillates	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Hydrotreated Light Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
Petroleum Gases, Liquified, Sweetened	Inhalation- Gas (4 hours)	Rat	LC50 277,000 ppm
Silicone Mixture	Dermal	Rabbit	LD50 > 19,400 mg/kg
Silicone Mixture	Ingestion	Rat	LD50 > 17,000 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
Petroleum Gases, Liquified, Sweetened	Professio nal judgemen t	No significant irritation

Silicone Mixture	Rabbit	No significant irritation

# **Serious Eye Damage/Irritation**

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
Petroleum Gases, Liquified, Sweetened	Professio	No significant irritation
	nal	
	judgemen	
	t	
Silicone Mixture	Rabbit	No significant irritation

#### **Skin Sensitisation**

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Guinea pig	Not sensitizing

#### **Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name		Value
Hydrotreated Light Petroleum Distillates	In Vitro	Not mutagenic
Petroleum Gases, Liquified, Sweetened	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Hydrotreated Light Petroleum Distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

# **Reproductive Toxicity**

# Reproductive and/or Developmental Effects

For the component/components, either no data are currently available or the data are not sufficient for classification.

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrotreated Light Petroleum Distillates	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	2 uruman
Hydrotreated Light Petroleum Distillates	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Hydrotreated Light Petroleum Distillates	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
Petroleum Gases, Liquified, Sweetened	Inhalation	cardiac sensitization	Causes damage to organs	similar compoun ds	NOAEL Not available	
Petroleum Gases, Liquified, Sweetened	Inhalation	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Petroleum Gases, Liquified, Sweetened	Inhalation	respiratory irritation	All data are negative		NOAEL Not available	

# Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
						Duration
Petroleum Gases,	Inhalation	kidney and/or	Some positive data exist, but the	Rat	NOAEL Not	
Liquified, Sweetened		bladder	data are not sufficient for		available	
			classification			

**Aspiration Hazard** 

Name	Value
Hydrotreated Light Petroleum Distillates	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient—is present below the threshold for labelling, an ingredient—is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

#### 12.1. Toxicity

#### **Ecotoxic to terrestrial invertebrates**

9.4B Terrestrial invertebrate toxicity

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Petroleum	68476-86-8		Data not			
Gases,			available or			
Liquified,			insufficient for			
Sweetened			classification			
Silicone	Trade Secret		Data not			
Mixture			available or			
			insufficient for			
			classification			
Proprietary	Trade Secret		Data not			
Resin			available or			
			insufficient for			
			classification			
Hydrotreated	64742-47-8		Data not			
Light			available or			
Petroleum			insufficient for			
Distillates			classification			

# 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Silicone Mixture	Trade Secret	Data not available or	N/A	N/A	N/A	N/A
Iviixture		insufficient for				
		classification				
Hydrotreated	64742-47-8	Data not	N/A	N/A	N/A	N/A
Light		available or				
Petroleum		insufficient for				

Distillates		classification					
Petroleum	68476-86-8	Data not	N/A	N/A	N/A	N/A	
Gases,		available or					
Liquified,		insufficient for					
Sweetened		classification					
Proprietary	Trade Secret	Data not	N/A	N/A	N/A	N/A	
Resin		available or					
		insufficient for					
		classification					

# 12.3: Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Silicone	Trade Secret	Data not	N/A	N/A	N/A	N/A
Mixture		available or				
		insufficient for				
		classification				
Hydrotreated	64742-47-8	Data not	N/A	N/A	N/A	N/A
Light		available or				
Petroleum		insufficient for				
Distillates		classification				
Petroleum	68476-86-8	Data not	N/A	N/A	N/A	N/A
Gases,		available or				
Liquified,		insufficient for				
Sweetened		classification				
Proprietary	Trade Secret	Data not	N/A	N/A	N/A	N/A
Resin		available or				
		insufficient for				
		classification				

#### 12.4. Mobility in soil

Please contact manufacturer for more details

#### 12.5 Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

See Section 11.1 Information on toxicological effects

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Disposal of the aerosol dispenser (that may or may not contain any residual substance), may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

# **SECTION 14: Transport Information**

New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport

UN No.: UN1950

**Proper Shipping Name: AEROSOLS** 

Class/Division: 2.1 Sub Risk: Not applicable. Packing Group: Not applicable.

**Special Instructions:** Limited quantity may apply

**Hazchem Code: 2YE** 

**IERG:** 49

International Air Transport Association (IATA) - Air Transport

UN No.: UN1950

**Proper Shipping Name:** AEROSOLS, FLAMMABLE

Class/Division: 2.1
Sub Risk: Not applicable.
Packing Group: Not applicable.

**International Maritime Dangerous Goods Code (IMDG) - Marine Transport** 

UN No.: UN1950

**Proper Shipping Name: AEROSOLS** 

Class/Division: 2.1
Sub Risk: Not applicable.
Packing Group: Not applicable.
Marine Pollutant: Not applicable.

**Special Instructions:** Limited quantity may apply

# **SECTION 15: Regulatory information**

HSNO Approval number HSR002515

Group standard name Aerosols (Flammable) Group Standard 2006 HSNO Hazard classification Refer to Section 2: Hazard identification

#### NZ Inventory of Chemicals (NZIoC) Status

All ingredients are listed on the New Zealand Inventory of Chemicals.

**HSNO Controls** 

Approved handler test certificate Class 2, required when present in quantities greater than 3,000 L (aggregate

water capacity)

Location and transit Depot certification test 3,000 L (aggregate water capacity)
Hazardous atmosphere zone 3,000 L (aggregate water capacity)

Fire extinguishers One required for 3,000 L (aggregate water capacity)

Emergency response plan 3,000 L (aggregate water capacity)

Secondary containment Not required Tracking Not required

Warning signage 3,000 L (aggregate water capacity)

# **SECTION 16: Other information**

#### **Revision information:**

No revision information

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit

for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: http://solutions.3mnz.co.nz